

### Pilot Scale CO<sub>2</sub> EOR in Mississippian Carbonate Reservoir at Wellington Field in South-Central Kansas


Yevhen Holubnyak, Willard Watney, Jason Rush, Mina Fazelalavi, and Dana Wreath

13<sup>th</sup> International Conference on Greenhouse Gas Control Technologies

Lausanne, Switzerland

November 16, 2016





### Participants
















**Schlumberger** Petrel

### **CO**, Sources Suitable for EOR



Ethanol and Biodiesel Plant Activity in Kansas


- \* Permitted and Permit Pending codes refer to KDHE Bureau of Air and Radiation - Air Construction permits.
- Permit Pending\*: 1 plants, 60 MGY
- Idle: 0 plants, 0 MGY  $\times$

- Permit Pending\*: 0 plants, 0 MGY
- × Idle: 1 plant, 1.8 MGY


- Kansas holds more than 750 million **barrels** of technical CO<sub>2</sub>-EOR potential and ~240-370M metric tons of CO2 is required for recoverv
- Economic results based on Hall Gurney field suggest an aftertax project IRR of about 20%
- Access to the significant volumes of ethanol-based CO<sub>2</sub> in Nebraska


#### Kansas CO<sub>2</sub> Emissions


(From sources greater than 500,000 metric tons annually)




### Potential Recoverable Resources: Formations of Interest








### Potential Recoverable Resources: Mississippian Group



### Wellington Field, South KS




## Plan for CO<sub>2</sub> EOR Pilot

- Find, characterize, and prepare oil field
- Find CO<sub>2</sub> source
  - Initially, ethanol plant multiple sources
- Develop strategy for resource recovery through reservoir modeling
  - Several revisions
- Obtain a permit and drill a new injection well
- Organize surface infrastructure and deliver CO<sub>2</sub>
  Truck delivery
- Inject ~26,000 ~20,000 tones of CO<sub>2</sub> at 100-150 tones/day
- Monitor and manage CO<sub>2</sub> plume
- Vent produced CO<sub>2</sub>

### **Reservoir Characterization**

- Very old Neutron logs with or without resistivity logs for all wells
- 16 wells with complete suites of resistivity and porosity logs
- New wells drilled by KGS have a full set of modern logs
- Core is available from KGS #1-32
  - Porosity/permeability
  - Geochemistry
  - Geomechanical data
- 3D Seismic
- Formation fluids analysis







#### Injection Well Drilling and Coring

- Class II Well Permit - 30 days process
- ~100 ft of new new core
- 70 ft of ~23%  $\mathsf{S}_{\mathsf{or}}$
- 20% Phi
- 15-18 mD

## **Injection Well Logging**







### Well Tests

- Drill stem test
- Step rate test
- Interference test


### **Seismic Stratigraphy Using PSDM**




### **Improved Geologic Model**




#### **Capillary Pressure and Relative Permeability**





# **Fluid Properties**

- CO<sub>2</sub> Miscibility pressure is ~1650 psi
- Oil API gravity is 30°
- Oil composition
- Water composition
- PVT




### **Reservoir Modeling**

- Strategy for a flood
  - Monitoring optimization
  - Re-pressurization strategy for miscibility
  - $-CO_2$  movement
- Economic forecast
  - Sweep efficiency
  - Oil production
  - $-CO_2$  production




## Forecasted CO<sub>2</sub> Movement in Reservoir

#### Forecasted Pore-Pressure Distribution at the Start of CO<sub>2</sub> Injection Required miscibility pressure is ~1650




### Waterflood Strategy after CO<sub>2</sub> Injection





### **Operations: CO<sub>2</sub> Delivery and Surface Facilities**



### **Fluid Monitoring**







05/13/2016

+ Maximum

Меал

Median Lower 25%

Lower 5%

+ Minimum

Upper 95%

Upper 75%


Water chemistry 

- Alkalinity


— pH

- Cations/anions
- Microbial
- Production history
  - Oil/water
  - CO<sub>2</sub> account


### **Geochemical Monitoring: Field Alkalinity Progression**




### **Seismic Monitoring**



# Incremental oil production (subtracted 9 bbls/day) recorded at a pilot area filed battery



CO<sub>2</sub> production from all installed separators at producing wells and pilot area field battery. At the end of September, 2016, 3 months since CO<sub>2</sub> injection cessation, only ~12% of injected CO<sub>2</sub> was produced



# Summary

- Safe and efficient injection
  - No substantial deviations due to unforeseen circumstances (carbonate reservoir fracturing, temperature, pressure, etc.)
- Successful oil recovery
- Low CO<sub>2</sub> production/recovery
  - 13% of total injected CO<sub>2</sub> was lost to atmosphere since start of injection
- Manageable and conformable CO<sub>2</sub> plume

### **Acknowledgements & Disclaimer**

#### Acknowledgements

• The work supported by the U.S. Department of Energy (DOE) National Energy Technology Laboratory (NETL) under Grant DE-FE0002056 and DE-FE0006821, W.L. Watney and Jason Rush, Joint PIs. Project is managed and administered by the Kansas Geological Survey/KUCR at the University of Kansas and funded by DOE/NETL and cost-sharing partners.

#### Disclaimer

• This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

