



DIGITAL LOG

(785) 625-3858

Dual Compensated
Porosity Log

15-015-23.934-00-00

API No.

Company **Vess Oil Corporation**
 Well **Wilson "A" No.444**
 Field **El Dorado**
 County **Butler** State **Kansas**

Location

2176' FNL & 2310' FWL

Other Services
DIL
MEL

Sec: 9 Twp: 25S Rge: 5E

Permanent Datum Ground Level Elevation 1357
 Log Measured From Kelly Bushing 6 Ft. Above Perm. Datum
 Drilling Measured From Kelly Bushing

Elevation
K.B. 1363
D.F. 1363
G.L. 1357

Date 4/4/2012

Run Number Two

Type Log CNL / CDL

Depth Driller 2488

Depth Logger 2488

Bottom Logged Interval 2486

Top Logged Interval 250

Type Fluid In Hole Chemical

Salinity, PPM CL 1,300

Density 9.3

Level Full

Max. Rec. Temp. F 101

Operating Rig Time 4 1/2 Hours

Equipment -- Location 17 Hays

Recorded By C. Desaire

Witnessed By Roger Martin

Borehole Record				Casing Record			
Run No.	Bit	From	To	Size	Wgt.	From	To
1	12.25	00	257	8.625	24#	00	257
2	7.875	257	2488				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for using Log-Tech, Inc.
(785) 625-3858

East of Potwin KS to 40 Rd,
2 E, 1/4 N, E Into on first right

Database File: c:\warrior\data\vess_wilson a no.444\vesshd3.db
 Dataset Pathname: dil/vessstk
 Presentation Format: cdl
 Dataset Creation: Wed Apr 04 06:57:32 2012
 Charted by: Depth in Feet scaled 1:600

0	Gamma Ray	150
6	Caliper (GAPI)	16

30	Compensated Density		-10
2	Bulk Density		3
15000	Line Tension		0
2.625	DGA	3.425	-0.25
			Correction
			0.25
LSPD			





























