



**COMPENSATED DENSITY
NEUTRON
LOG**

Company	Castle Resources Inc.	Company	Castle Resources Inc.
Well	Sieker #1	Well	Sieker #1
Field	Chase - Silica	Field	Chase - Silica
County	Rice	County	Rice
State	Kansas	State	Kansas
Location:	1820' FSL & 1850' FWL	API # :	15 159 22742
Permanent Datum	SEC 34 TWP 19S RGE 10W	Ground Level	1782'
Log Measured From	KB 5' AGL	Elevation	1782'
Drilling Measured From	KB	Elevation	K.B. 1787' D.F. 1786' G.L. 1782'

Date	6-6-13
Run Number	One
Depth Driller	3380'
Depth Logger	3377'
Bottom Logged Interval	3353'
Top Log Interval	245'
Casing Driller	8 5/8" @ 315'
Casing Logger	315'
Bit Size	7 7/8"
Type Fluid in Hole	Chemical
Density / Viscosity	9.5/58
pH / Fluid Loss	8.0/10.5
Source of Sample	Pit
Rm @ Meas. Temp	.9@65degf
Rmf @ Meas. Temp	.68@65degf
Rmc @ Meas. Temp	1.08@65degf
Source of Rmf / Rmc	Calculated
Rm @ BHT	.52@112degf
Time Circulation Stopped	2:30 a.m.
Time Logger on Bottom	5:00 a.m.
Maximum Recorded Temperature	112degf
Equipment Number	T045
Location	Hays, KS.
Recorded By	L. Smith
Witnessed By	Mr. Jerry Green

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thanks for using Gemini Wireline LLC Hays, KS. (785-625-1182)



Main Pass

Database File: crsieker#1oh.db
 Dataset Pathname: pass2.1
 Presentation Format: kcdnl
 Dataset Creation: Thu Jun 06 06:14:32 2013 by Calc Open-Case 100827
 Charted by: Depth in Feet scaled 1:240

0	GR (GAPI)	150
6	DCAL (in)	16
6	BOREID (in)	16

30	NPOR (pu)	-10
30	DPOR (pu)	-10
70	DPOR (pu)	30

TBHV (ft3)	-0.25	RHOC (g/cc)	0.25
	8000	LTEN (lb)	0
			ABHV (ft3)





