Contents KBFDA JACK
Well 15/9-19 A
Field LUNDIN
County OSEBERG SØR
State
Country NORWAY

DUAL INDUCTION SLIMPULSE

Run 1
Date 06-MAY-13
Depth Driller 3400 m
Depth Logger 3400 m
Bottom Logged Interval 3400 m
Top Logged Interval 1750 m
Casing Driller 1750 m @ 1750 m
Casing Logger 1750 m @ 1750 m
Bit Size 8.5 in
Drilling Fluid Type WBM
Density 1.45 g/cm³
Viscosity 60 s
Fluid Loss 3.6 cm³
Resistivity 0.1 ohmm @ 60 °C
Source of Sample FLOWLINE
Rm @ Measured Temperature 0.1 ohmm @ 60 °C
Rmf @ Measured Temperature 0.1 ohmm @ 60 °C
Rmc @ Measured Temperature 0.1 ohmm @ 60 °C
Source of Rmf and Rmc MEASURED
Rm @ BHT 0.1 ohmm @ 60 °C
Time Since Circulation 12 hr
Time on Bottom 06-MAY-13 23:00
Maximum Recorded Temperature 60 °C
Equipment Number 1301
Location 58° 26' 29.64" N 2° 31' 29.64" E
Elevation 0 m
Permanent Datum MEAN SEA LEVEL
Elevation of Kelly Bushing 25 m
Elevation of Derrick Floor 25 m
Elevation of Ground Level -95 m
Water Depth 95 m

(-) Denotes Inferred Value

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not, guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our standard terms and conditions as set out in our current Price Schedule.

Comments

DIG-BTM

OBDH SHARELES

2" DIL SECTION

Database File isis7.6TAP.gbh Norton.db
Dataset Pathname PASS#1.1
Presentation Format dil-dsi-bht
Dataset Creation Wed 15-JAN-97 20:04
Charted by Depth in Feet scaled 1:240

GR (GAPI) 150 | RILD (Ohm-m) 0.2 2000 | RILM (Ohm-m) 0.2 2000 | RLL3 (Ohm-m) 0.2 2000 | SFLU (Ohm-m) 0.2 2000 | CILD (mmho/m) 0 1000

Database File isis7.6TAP.gbh Norton.db
Dataset Pathname PASS#1.2
Presentation Format dil-dsi-bht
Charted by Depth in Feet scaled 1:240

GR (GAPI) 150 | RILD (Ohm-m) 0.2 2000 | RILM (Ohm-m) 0.2 2000 | RLL3 (Ohm-m) 0.2 2000 | SFLU (Ohm-m) 0.2 2000 | CILD (mmho/m) 0 1000

Sensor Offset (ft) Schematic Description Length (ft) O.D. (in) Weight (lb)

Cable Head/Quad
Cable Quad/Mud

CILD 19.00
SFL 19.00

DIL-GBAR-13MC
Dual Induction-Gamma Ray

21.36 4.50 345.00

CILM 7.00

RILD 1.67

Depths
Scale 1:240
Log Interval 3400 to 1750

Dataset isis7.6TAP.gbh Norton.db /MainHeadDIS.dataset
Run Number 1
Logging Unit 1