Client: Kansas Geological Survey
DOE Mesaverde Petrophysics Project

Well: The Wyoming Mines, Inc.
Operator: CER Corporation
Location: Sec 6 T20N R79W 6th PM
Formation: Shoshonite Group
Core depth: 4870.8147 gross
Core Lab Job No: 730-89488 DIGS-CWC 7-849
Described by: John T. Weitz, Danielle Stricker

Lease: WWU 2 Superior
County: Carbon State: Wyoming
Basin: Piceance
Log depth 4650-4840 ft = Core depth -10 ft
Core Lab Bench: Golden
Core Quality: Good Status: 1/3 Condition Excellent

Depth (in ft): Lithology 1 / Lithology 2 / Color (wet): Lithology and sedimentary structures: Energy Orgn Lg, Sg, Ltb, Stb, Xb, Cgl, Mdst, Wkst, Pkst, Grst, Bfst, Gnst, Rudst, Flmst, Sltst, Vfsd, Fsd, Msd, Csd, Vcsd, Gran, Clyst, Coal, Anh, Mud, Silt, Clay, Peat, Tuff, Ash, Digital Log Curves: GR, SP, RES, DEN, Sonic, Sat, Cal, Environment of deposition

CONTINUED FROM PART 1
NO CORE 6969.5-7090'
Log depth 7070-7400 ft = Core - 7 ft

Williams Fork Formation
Paludal interval of Lorenz, et al.
Geotek Laboratories 6969 reported

Channel fill, estuarine?
Raised mire
Channel abandonment
Channel fill, tidally influences estuarine?
Raised mire
Channel fill, estuarine
Channel fill, tidally influenced
Raised mire
Bay fill
Raised mire
Bay fill
Channel abandonment
Channel fill, tidally influences estuarine
Raised mire
Lagoon fill
Raised mire
Channel abandonment
Channel fill, tidally influenced estuarine
Channel fill, tidally influenced estuarine
Raised mire
Channel abandonment

Iles Formation
Cozzette Member

NO CORE 7389.5-7820'
Log depth 7810-7910 ft = Core - 6 ft

Channel abandonment or lagoon fill
Channel fill, tidally influences estuarine
Marine shoreface
Marine inner shelf

Iles Formation
Corcoran Member

NO CORE 7905.5-8091.5'
Log depth 8090-8190 ft = Core - 6 ft

Channel fill and abandonment, tidally influences estuarine
Raised mire
Channel fill and abandonment